

Rovsco's ROV Hot Stab is designed to fully comply with the geometry required for industry standard, ISO 13628-8, and API 17-H.

The Hot Stab has two independent Pressure Circuits, designed to work with 10,000 psi working pressure. It comes with vent holes that prevent pressure lock when installing or retrieving Hot Stab during operation.

Main Body is fabricated from Nitronic 60. Handles and fasteners are fabricated from 316 stainless.

Handles with wire rope extension are fully compliant, and independent from Hot Stab main body.

Features:

- ◆ Meets ISO 13628-8, & API-17H Requirements
- ◆ Dual Port, two independent pressure circuits
- ◆ 10,000 Psi WP
- ◆ 1/4" NPT female connections
- ◆ Nitronic 60 SS main body
316 stainless Handles and fasteners
- ◆ Seals compatible with water-based & oil-based hydraulic fluids
- ◆ Handles are independent from Hot Stab body
- ◆ Several Hot Stab Handle Configurations available



ROVSCO[®], Inc.

5263 Barker Cypress Road, Suite 600
P.O. Box 218570
Houston, Texas 77218-8570
U.S.A.
Tel: +1 281 858 6333
Fax: +1 281 858 6363
Email: sales@rovSCO.com
<http://www.rovSCO.com>