



Extreme Low Light Monochrome Camera

The Rovsco line of underwater video products, offers a complete range of highest quality color and extremely low light monochrome video cameras. These cameras are designed to provide exceptionally clear video images from the deep ocean. They are built to withstand the deepsea environment and work flawlessly providing many years of service.

The Rovsco Pilot 3000 video camera is based on CCD technology. Packaged in a titanium housing, it provides high quality monochrome video at extremely low light conditions (.00015 lux). Rated to 3000 meter depth for today's deep ocean ROVs, it's a perfect choice to operate in low light conditions. The camera provides 570 TV lines of video resolution and is equipped with a wide angle lens to provide a great coverage. The camera is fitted with a water corrected acrylic port which has similar refractive properties to that of seawater. This makes it a preferred choice for viewing in seawater conditions.

PAL or NTSC



Features

- ♦ Sensitivity (.00015 lux)
- ♦ High Resolution (570 TV Lines)
- Water Corrected Viewport
- ♦ Wide Angle
- ♦ Titanium Housing
- ♦ 3000m Depth

Applications

- ROVs
- ♦ AUVs
- Homeland Security
- ♦ Surveillance



Pilot 3000

Specification

Electronics

Image Device½" Interline Transfer CCDResolution570 TV Lines (minimum)Pixels811 (H) x 508 (V) (EIA)

795 (H) x 596 (V) (CCIR)

Sensitivity $1.4 \times 10^{-4} \text{ lux (faceplate)}$

Iris Auto
Signal to Noise Ratio >50 db

Video Output 1.0 V p-p composite

Voltage 11-30 VDC *Standard Connector Burton 5506-1508

*Other connectors available

Optical

Focal Length 3.6 mm, F1.0

Field of View (in water) 82.4° Horizontal, 65.7° Vertical, 94.6° Diagonal

Focus Fixed (5 inch to infinity)

Environmental

Storage Temperature -10° C to $+50^{\circ}$ C Operating Temperature 0° C to $+40^{\circ}$ C Depth Rating 3000m

Mechanical

Housing Material Titanium

Size Length: 8.1 inch (205.7 mm) excluding connector

Diameter: Main Body: 3.3 inch (84 mm)

Front End: 3.63 inch (92 mm)

Weight in Air 2.58 kg Weight in water 0.95 kg

All specifications are subject to change without notice in line with Rovsco's policy of ongoing product development

ROVSCO[®], Inc.

5263 Barker Cypress Road, Suite 600 P.O. Box 218570 Houston, Texas 77218-8570 U.S.A.

T: +1 281 858 6333 F: +1 281 858 6363 E: sales@rovsco.com http://www.rovsco.com

ROVSCO ASIA Pte Ltd

11 - Changi South, Street No.1 Suite 01-03 Singapore 486787

T: (+65) 6546 6526 F: (+65) 6546 5625 E: sales@rovscoasia.com http://www.rovscoasia.com